


Femtocell sCELL-F4240-ID



# sCELL-F4240-ID

## LTE Enterprise Femtocell

2 x 2 MIMO

2 x 2x 250mw

2\*64 Concurrent Users

2\*192 RRC Connected Users

The F4240 is CBRS dual carrier LTE small cells targeted at indoor enterprise environments. The units can be installed by both end-users in “Plug-and-Play” mode and technicians in planned deployment. With 2\*2\*250mW output power of each cell and high-performance such as carrier aggregation, the F4240 can help mobile operators improve coverage and capacity with minimum cost.

Copyright © 2023 SUNWAVE All rights reserved.

## Femtocell sCELL-F4240-ID

## KEY FEATURES

- Standard LTE bands: TDD bands 42/43/48
- Peak data rate of each cell (20MHz)
  - DL 130Mbps (256QAM,SF2)
  - UL 30Mbps (64QAM,SF1)
- Peak data rate of carrier aggregation(20MHz)
  - DL 260Mbps (256QAM,SF2)
  - UL 60Mbps (64QAM,SF1)
- Maximum 2\*64 VoLTE users, 2\*64 RRC active users and 2\*192 RRC connected users
- All IP based backhaul, many IP backhaul methods can be used, including RJ45 Ethernet, SFP
- Plug-and-play with SON features, including self-configuration, self-optimization, self-healing
- Local Web GUI management, network management with HeNB management server
- Compact and beautiful design, supplied with high performance integrated antennas.
- PoE supported. Lower power consumption to reduce OPEX.

## APPEARANCE



## HARDWARE SPECIFICATIONS

Chipset	Qualcomm: FSM9955 + 2*FTR8950
LTE Mode	TDD
Frequency Bands	TDD: 42/43/48
Channel Bandwidth	5/10/15/20 MHz
Characteristic Impedance	50Ω
Number of RF Ports	6 RF (4*ANT, SNF, GPS)
Max Output Power	24 dBm / antenna
Transmitter Performance	36.141, Home BS compliance
Receiver Performance	36.141, Home BS compliance
Synchronization	GPS, IEEE 1588v2 PTP, Network Listening
Backhaul	- 1 RJ45 Ethernet (10/100/1000 Auto-negotiating) - SFP

Copyright © 2023 SUNWAVE All rights reserved.

## Femtocell sCELL-F4240-ID

<b>Power Supply</b>	- 90 ~ 254V AC to 12V DC - PoE+ (IEEE 802.3at standard)
<b>Dimensions (H*W*D)</b>	220*220*40 mm   8.67*8.67*1.57 in
<b>Weight</b>	< 1kg
<b>Power Consumption (W)</b>	< 20W
<b>Antenna</b>	-Internal: 3 dBi <120° -External: 5 dBi omni antenna
<b>Installation</b>	Desktop, Ceiling or Wall mounted
<b>Material</b>	Top:plastic Bottom:cast-aluminium

## SOFTWARE SPECIFICATIONS

<b>LTE Standard</b>	3GPP Release 12
<b>Peak Data Rate (20MHz BW) of each cell</b>	- DL 130Mbps (256QAM,SF2) - UL 30Mbps (64QAM,SF1)
<b>Peak Data Rate (20MHz BW) of carrier aggregation</b>	- DL 260Mbps (256QAM,SF2) - UL 60Mbps (64QAM,SF1)
<b>Modulation</b>	- DL:QPSK,16QAM,64QAM,256QAM - UL: QPSK,16QAM,64QAM
<b>Max User Number</b>	2 * 64 VoLTE users 2 * 64 RRC active users 2 * 192 RRC connected users
<b>SON Features</b>	-Self-configuration: Automatic Neighbor Relation (ANR) Physical Cell Identity (PCI) Auto-configuration Radio Environment Management (REM) S1/X2 auto configuration RACH channel self-configuration Channel Selection Transmission Power Management -Self-optimization: MRO, MLB, CCO, RACH organization -Self-healing: Automatic cell outage detection Software recovery
<b>Maintenance</b>	Online status monitoring and management Performance management, KPI recording Fault management, Alarm reporting Configuration management

## Femtocell sCELL-F4240-ID

	Local or remote software upgrade User information tracing
<b>QoS</b>	3GPP standard QCI
<b>MTBF</b>	≥ 150000 hours
<b>MTTR</b>	≤ 1 hour

## ENVIRONMENTAL SPECIFICATIONS

<b>Operating Temperature</b>	-5°C ~ +45°C   +23 °F ~ +113 °F
<b>Storage Temperature</b>	-45°C ~ +70°C   +49°F ~ +158 °F
<b>Operating Humidity</b>	5% to 95%
<b>Storage Humidity</b>	5% to 95%
<b>IP Rating</b>	IP30
<b>Housing Self-extinguishing Class</b>	V-0
<b>Shock when packaged</b>	ETSI 300 019 1-2 (class 2.3) NEBS GR63
<b>Shock unpackaged</b>	Max Drop Height: 750mm in hard ground

Contact Us Today

[en.sunwave.com](http://en.sunwave.com)